

NASA TECH BRIEF

Goddard Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Thermal Heliotrope: A Passive Sun-Tracker

The problem:

To design a simple, inexpensive, sun tracking system. Conventional electromechanical tracking systems are complex and expensive, making a passive system more desirable.

ment with temperature change, and acts as the driving element of the device. The control mechanism, a concentric shading mechanism containing a bimetallic sensor coil, controls the tracking rate and provides for the reset cycle.

How it's done:

The shades are mechanically synchronized with an escapement mechanism consisting of an escapement arm actuated by a sensor pin. For each heating and cooling cycle of the sensor coil, the escapement slips two increments. When the slots in the shades align, the bimetallic coil is illuminated, the sensor pin actuates the escapement arm, and the array rotates one increment. The shades are then closed and the coil begins to cool. During the cool-down period, another escapement motion occurs and the coil again becomes illuminated, repeating the cycle. The cycle sequence continues until the lock-on slat, which is coplanar with the surface to be oriented, is normal to the sun. In this position, the sensor coil is shaded, regardless of slot alignment, and no further rotation will occur until the control surface becomes misaligned. A typical application of a simple reset type of thermal heliotrope is presented in Figure 2.

The critical design parameter is the size of the coil. For maximum available torque, the coil should be relatively wide, since torque is directly proportional to the width and the square of thickness. However, an important tradeoff is concerned because transient heating and cooling rates are inversely proportional to thickness. The design approach, then, sizes the coil thickness to provide the necessary thermal response, and maximizes the

(continued overleaf)




Figure 1.

The solution:

A passive thermal heliotrope tracker (see Fig. 1) capable of continuous sun tracking. The device consists of two main components: a helical bimetallic coil and a control mechanism. The bimetallic motor coil produces the torque and angular displacement

width within the limits of the physical size and diameter of the winding.




Figure 2.

Note:

Requests for further information may be directed to:

Technology Utilization Officer
Goddard Space Flight Center
Greenbelt, Maryland 20771
Reference: B71-10260

Patent status:

This invention is owned by NASA, and a patent application has been filed. Royalty-free nonexclusive licenses for its commercial use will be granted by NASA. Inquiries concerning license rights should be made to:

Patent Counsel
Mail Code 204
Goddard Space Flight Center
Greenbelt, Maryland 20771

Source: R. C. Byxbee of
Lockheed Missiles and Space Co.
under contract to
Goddard Space Flight Center
(GSC-10945)